

FOR USE IN AMBIENT AND GENERAL LIGHTING APPLICATIONS



PROJECT TYPE PART NUMBER

FEATURES -

Energy efficient replacement from fluorescent technology

150,000 hr + L70

Philips Fortimo LED Boards

Dimming options available upon request

Wide range of lumen and wattage packages available

149 lumen per watt delivered / 82+ CRI

Color Tuning options available



SPECIFICATIONS

CONSTRUCTION

All aluminum construction minimizes weight and maximizes thermal performance of the LED light engine. All parts are painted with a matte white paint to provide soft, even illumination.

MOUNTING

Fixture is designed for surface mounting only.

LEDS

Best efficacy of mid-level power LEDs, 80+ CRI, utilizes aluminum substrate to provide superior thermal management

ELECTRICAL

LED Light Engine designed for reliability and long life operation Standard 0-10V dimming to 1% 120 - 277 V standard

CONTROLS

Individual or grouping control with many solutions available Consult factory for specific requirements

LISTINGS

DesignLights Consortium Premium qualified, see DLC QPL
ETL safety certified for damp locations
Standard 5 year warranty / 10 year warranty available upon request













ORDERING INFORMATION -

						SM	
STYLE	SIZE	LIGHT ENGINE			COLOR TEMP	STANDARD	OPTIONS
F FIXTURE	14LE 1' x 4' 22LE 2' x 2' 24LE 2' x 4'	1' X 4' F4X5 16W 2261 LUMENS F4L0 20W 2758 LUMENS F4L5 25W 3434 LUMENS F4L8 28W 3817 LUMENS F4N2 32W 4356 LUMENS F4N6 36W 4896 LUMENS	2' X 2' L2X6 16W 2203 LUMENS L2X8 18W 2520 LUMENS L2L2 22W 3087 LUMENS L2L4 24W 3364 LUMENS L2L8 28W 3922 LUMENS L2N0 30W 4198 LUMENS	2' X 4' F4L0 22W 3277 LUMENS F4L5 25W 3697 LUMENS F4L8 28W 4092 LUMENS F4N2 32W 4644 LUMENS F4N6 36W 5192 LUMENS F4M0 40W 5763 LUMENS	35 3500K 40 4000K 50 5000K 2765 2700K - 6500K (ADJUSTABLE)	SM SURFACE MOUNT	SD STEP DIMMING (BI LEVEL OR TRI LEVEL) LVD120 / 277 120V / 277V LINE VOLTAGE DIMMING D PREWIRED FOR 0-10V DIMMING EM EMERGENCY BACKUP INCLUDED (6W STANDARD) FR FROSTED LENS DL DUAL LENS DESIGN RGBW COLOR CHANGING WITH VARIOUS CONTROL OPTIONS AVAILABLE
		41W 5515 LUMENS	33W 4538 LUMENS				

CUSTOM OPTIONS

ADDITIONAL GRAPHICS



Square Lens option









^{* 2765} is only for color select options using a compatible control system